

CLAIMS:

1 1. A non-invasive health monitor device comprising:
2 a processor;
3 a processor readable storage medium;
4 code recorded in the processor readable storage medium to create a first array of data
5 based on discretely recorded time events in which each element of the first array is
6 representative of a time when an event took place;
7 code recorded in the processor readable storage medium to create a second array of
8 data in which each element of the second array is an interval representative of the difference
9 between successive elements of the first array;
10 code recorded in the processor readable storage medium to create a third array of data
11 in which each element of the third array is a delta interval representative of the difference
12 between successive elements of the second array;
13 code recorded in the processor readable storage medium to perform a fast fourier
14 transform (FFT) to obtain power spectrum data representative of the third array; and
15 code recorded in the processor readable storage medium to integrate the power
16 spectrum data over frequency ranges of interest to obtain discrete power values for said
17 frequency ranges of interest.

1 2. A non-invasive health monitor device to assist in cardiac evaluation comprising:
2 a processor;
3 a processor readable storage medium;

4 code recorded in the processor readable storage medium to create a first array of heart
5 vibrations based on discretely recorded heartbeats in which each element of the first array is
6 representative of a time when a heartbeat took place;

7 code recorded in the processor readable storage medium to create a heart period array
8 in which each element is a heart period interval representative of the difference between
9 successive heartbeats of the first array of heart vibrations;

10 code recorded in the processor readable storage medium to create a delta heart period
11 interval array in which each element is a delta heart period interval representative of the
12 difference between successive elements of the heart period interval array;

13 code recorded in the processor readable storage medium to perform a fast fourier
14 transform (FFT) to obtain power spectrum data representative of the delta heart period
15 interval array; and

16 code recorded in the processor readable storage medium to integrate the power
17 spectrum data over one or more frequency ranges of interest to obtain discrete power values
18 for said one or more frequency ranges of interest.

1 3. The non-invasive health monitor device of claim 2 wherein the frequency ranges of
2 interest include a low frequency (LF) range, a high frequency (HF) range, and a very high
3 frequency (VHF) range.

1 4. The non-invasive health monitor device of claim 3 further comprising:

2 code recorded in the processor readable storage medium to calculate a total power,
3 TP, value that is the sum of the LF, HF, and VHF power values.

- 1 5. The non-invasive health monitor device of claim 3 further comprising:
2 code recorded in the processor readable storage medium to calculate a power ratio
3 value that is equal to LF / HF .

- 1 6. The non-invasive health monitor device of claim 4 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized LF
3 power value that is equal to LF / TP .

- 1 7. The non-invasive health monitor device of claim 4 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized HF
3 power value that is equal to HF / TP .

- 1 8. The non-invasive health monitor device of claim 4 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized
3 VHF power value that is equal to VHF / TP .

- 1 9. The non-invasive health monitor device of claim 3 wherein the LF range is approximately
2 .04 to .15 Hz.

- 1 10. The non-invasive health monitor device of claim 3 wherein the HF range is
2 approximately .15 to 0.4 Hz.

- 1 11. The non-invasive health monitor device of claim 3 wherein the VHF range is

2 approximately 0.4 to 1.0 Hz.

1 12. A non-invasive health monitor device to assist in respiration evaluation comprising:

2 a processor;

3 a processor readable storage medium;

4 code recorded in the processor readable storage medium to create a first array of
5 respiration events based on discretely recorded body motions in which each element of the
6 first array is representative of a time when a respiration event took place;

7 code recorded in the processor readable storage medium to create a respiration period
8 interval array in which each element is a respiration period interval representative of the
9 difference between successive elements of the first array of respiration events;

10 code recorded in the processor readable storage medium to create a delta respiration
11 period interval array in which each element is a delta respiration period interval
12 representative of the difference between successive elements of the respiration period
13 interval array;

14 code recorded in the processor readable storage medium to perform a fast fourier
15 transform (FFT) to obtain power spectrum data representative of the delta respiration period
16 interval array; and

17 code recorded in the processor readable storage medium to integrate the power
18 spectrum data over a defined range of interest to obtain a discrete power value.

1 13. A non-invasive health monitor device to assist in cardiac evaluation comprising:

2 a processor;

3 a processor readable storage medium;

4 code recorded in the processor readable storage medium to create an array of first

5 heart vibrations based on discretely recorded heartbeats in which each element of the first

6 array is representative of a time when a first heart vibration of a heartbeat took place;

7 code recorded in the processor readable storage medium to create an array of second

8 heart vibrations having an element to element association with the array of first heart

9 vibration, said array of second heart vibrations representative of a time when a second heart

10 vibration of a heartbeat took place;

11 code recorded in the processor readable storage medium to create a ventricular systole

12 interval array in which each element is an interval representative of the time difference

13 between the second and first heart vibrations of each heartbeat in the second and first heart

14 vibration arrays;

15 code recorded in the processor readable storage medium to create a delta ventricular

16 systole interval array in which each element is a delta ventricular systole interval

17 representative of the difference between successive elements of the ventricular systole

18 interval array;

19 code recorded in the processor readable storage medium to perform a fast fourier

20 transform (FFT) to obtain power spectrum data representative of the delta ventricular systole

21 interval array; and

22 code recorded in the processor readable storage medium to integrate the power

23 spectrum data over one or more frequency ranges of interest to obtain discrete power values

24 for said one or more frequency ranges of interest.

1 14. The non-invasive health monitor device of claim 13 wherein the power spectrum
2 frequency ranges of interest include a low frequency (LF) range, a high frequency (HF)
3 range, and a very high frequency (VHF) range.

1 15. The non-invasive health monitor device of claim 14 further comprising:
2 code recorded in the processor readable storage medium to calculate a total power,
3 TP, value that is the sum of the LF, HF, and VHF power values.

1 16. The non-invasive health monitor device of claim 16 further comprising:
2 code recorded in the processor readable storage medium to calculate a power ratio
3 value that is equal to LF / HF .

1 17. The non-invasive health monitor device of claim 15 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized LF
3 power value that is equal to LF / TP .

1 18. The non-invasive health monitor device of claim 15 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized HF
3 power value that is equal to HF / TP .

1 19. The non-invasive health monitor device of claim 15 further comprising:
2 code recorded in the processor readable storage medium to calculate a normalized
3 VHF power value that is equal to VHF / TP .

1 20. The non-invasive health monitor device of claim 14 wherein the LF range is
2 approximately 0 to 0.15 Hz.

1 21. The non-invasive health monitor device of claim 14 wherein the HF range is
2 approximately 0.15 to 0.4 Hz.

1 22. The non-invasive health monitor device of claim 14 wherein the VHF range is
2 approximately 0.4 to 1.0 Hz.

1 23. A non-invasive health monitor device comprising:
2 a processor;
3 a processor readable storage medium;
4 code recorded in the processor readable storage medium to create a first array of data
5 based on discretely recorded time events in which each element of the first array is
6 representative of a time when an event took place;
7 code recorded in the processor readable storage medium to create a second array of
8 data in which each element of the second array is an interval representative of the difference
9 between successive elements of the first array;
10 code recorded in the processor readable storage medium to create a third array of data
11 in which each element of the third array is a delta interval representative of the difference
12 between non-successive elements of the second array;
13 code recorded in the processor readable storage medium to perform a fast fourier
14 transform (FFT) to obtain power spectrum data representative of the third array; and

15 code recorded in the processor readable storage medium to integrate the power
16 spectrum data over frequency ranges of interest to obtain discrete power values for said
17 frequency ranges of interest.

1 24. A method of monitoring health non-invasively comprising:
2 creating a first array of data based on discretely recorded time events in which each
3 element of the first array is representative of a time when an event took place;
4 creating a second array of data in which each element of the second array is an
5 interval representative of the difference between successive elements of the first array;
6 creating a third array of data in which each element of the third array is a delta
7 interval representative of the difference between successive elements of the second array;
8 performing a fast fourier transform (FFT) on the third array to obtain power spectrum
9 data representative of the third array; and
10 integrating the power spectrum data over frequency ranges of interest to obtain
11 discrete power values for said frequency ranges of interest.

1 25. A method of monitoring health non-invasively to assist in cardiac evaluation comprising:
2 creating a first array of heart vibrations based on discretely recorded heartbeats in
3 which each element of the first array is representative of a time when a heartbeat took place;
4 creating a heart period array in which each element is a heart period interval
5 representative of the difference between successive elements of the first array of heart
6 vibrations;
7 creating a delta heart period interval array in which each element is a delta heart

8 period interval representative of the difference between successive elements of the heart
9 period interval array;
10 performing a fast fourier transform (FFT) on the delta heart period interval array to
11 obtain power spectrum data representative of the delta heart period interval array; and
12 integrating the power spectrum data over one or more frequency ranges of interest to
13 obtain discrete power values for said one or more frequency ranges of interest.

1 26. The method of claim 25 wherein the frequency ranges of interest include a low
2 frequency (LF) range, a high frequency (HF) range, and a very high frequency (VHF) range.

1 27. The method of claim 26 further comprising:
2 calculating a total power, TP, value that is the sum of the LF, HF, and VHF power
3 values.

1 28. The method of claim 26 further comprising:
2 calculating a power ratio value that is equal to LF / HF.

1 29. The method of claim 27 further comprising:
2 calculating a normalized LF power value that is equal to LF / TP.

1 30. The method of claim 27 further comprising:
2 calculating a normalized HF power value that is equal to HF / TP.

1 31. The method of claim 27 further comprising:

2 calculating a normalized VHF power value that is equal to VHF / TP .

1 32. The method claim 26 wherein the LF range is approximately .04 to .15 Hz.

1 33. The method of claim 26 wherein the HF range is approximately .15 to 0.4 Hz.

1 34. The method of claim 26 wherein the VHF range is approximately 0.4 to 1.0 Hz.

1 35. A method of monitoring health non-invasively to assist in respiration evaluation
2 comprising:

3 creating a first array of respiration events based on discretely recorded body motions
4 in which each element of the first array is representative of a time when a respiration event
5 took place;

6 creating a respiration period interval array in which each element is a respiration
7 period interval representative of the difference between successive elements of the first array
8 of respiration events;

9 creating a delta respiration period interval array in which each element is a delta
10 respiration period interval representative of the difference between successive elements of
11 the respiration period interval array;

12 performing a fast fourier transform (FFT) on the delta respiration period interval array
13 to obtain power spectrum data representative of the delta respiration period interval array;

14 and

15 integrating the power spectrum data over a low frequency (LF) range of interest to
16 obtain a discrete power value.

1 36. The method of claim 35 wherein the LF range is approximately .04 to 0.3 Hz.

1 37. A method of monitoring health non-invasively to assist in cardiac evaluation comprising:

2 creating a first array of heart vibrations based on discretely recorded heartbeats in
3 which each element of the first array is representative of a time when a ventricular heart
4 vibration of a heartbeat took place;

5 creating a second array of heart vibrations having an element to element association
6 with the first array of heart vibrations, said second array of heart vibrations representative of
7 a time when a systolic heart vibration of a heartbeat took place;

8 creating a ventricular systole interval array in which each element is an interval
9 representative of the time difference between the second and first heart vibrations of each
10 heartbeat in the second and first arrays;

11 creating a delta ventricular systole interval array in which each element is a delta
12 ventricular systole interval representative of the difference between successive elements of
13 the ventricular systole interval array;

14 performing a fast fourier transform (FFT) on the delta ventricular systole interval
15 array to obtain power spectrum data representative of the delta ventricular systole interval
16 array; and

17 integrating the power spectrum data over one or more frequency ranges of interest to
18 obtain discrete power values for said one or more frequency ranges of interest.

1 38. The method of claim 37 wherein the frequency ranges of interest include a low
2 frequency (LF) range, a high frequency (HF) range, and a very high frequency (VHF) range.

1 39. The method of claim 38 further comprising:
2 calculating a total power, TP, value that is the sum of the LF, HF, and VHF power
3 values.

1 40. The method of claim 38 further comprising:
2 calculating a power ratio value that is equal to LF / HF .

1 41. The method of claim 39 further comprising:
2 calculating a normalized LF power value that is equal to LF / TP .

1 42. The method of claim 39 further comprising:
2 calculating a normalized HF power value that is equal to HF / TP .

1 43. The method of claim 39 further comprising:
2 calculating a normalized VHF power value that is equal to VHF / TP .

1 44. The method of claim 38 wherein the LF range is approximately .04 to .15 Hz.

1 45. The method of claim 38 wherein the HF range is approximately .15 to 0.4 Hz.

1 46. The method of claim 38 wherein the VHF range is approximately 0.4 to 1.0 Hz.

1 47. A method of monitoring health non-invasively comprising:

2 creating a first array of data based on discretely recorded time events in which each
3 element of the first array is representative of a time when an event took place;

4 creating a second array of data in which each element of the second array is an
5 interval representative of the difference between successive elements of the first array;

6 creating a third array of data in which each element of the third array is a delta
7 interval representative of the difference between non-successive elements of the second
8 array;

9 performing a fast fourier transform (FFT) on the third array of data to obtain power
10 spectrum data representative of the third array of data; and

11 integrating the power spectrum data over frequency ranges of interest to obtain
12 discrete power values for said frequency ranges of interest.